

## MALERKOTLA, PUNJAB www.dasmesh.com

## YOUR PARTNER IN FARMING

...........









## SPECIAL FEATURES

- HIGH SPEED SINGLE LEVER GEAR BOX
- STAINLESS STEEL FEEDER AND ELEVATOR
- MUSIC SYSTEM WITH MOBILE CHARGER
- ADJUSTABLE STEERING
- DISK BREAK SYSTEM
- BIG DIESEL TANK
- HIGH QUALITY STOVING PAINT
- CRYSTAL HEADLIGHTS
- HEAVY DUTY PIPE REEL



SELF PROPELLED COMBINE HARVESTER

DASMESH 9100

## **ENGINE**

H6ETIC3RD22 BS-III Ashok Levland Model

101 HP @ 2200 rpm Power

No of Cylinder Six

Combination of Dry Air Cleaner Water Cooled

Cooling System

CLUTCH

Single, Heavy Duty Dry Clutch Type of Clutch

Dia (mm) 330 (mm)

**TRANSMISSION** 

3 Forward 1 Reverse No. of Gears Gears Speeds (Km./Hr.) Forward 1st Gear 2nd Gear 8 3rd Gear 10 30

**CUTTER BAR** 

Reverse

for Wheat, Paddy & Others

Width 14 Feet Cutting Height (mm) 55-1250 mm

No. of Blades 57 No. of Guards 58 Stroke (mm) 89 25-50 Reel (rpm) Dia (mm) 1016

THRESHING MECHANISM

**Thresher Drum** Wheat (Rasp Bar) Paddy (Peg Tooth)

Width (mm) 1257 1258 Dia of Thresher Drum (mm) 602 606

Speed (rpm) 562-960

Speed Adjustment By Means of Mechanical Variator

CONCAVE

Clearance **Paddy** Wheat Front (mm) 18-30 8-46 Rear (mm) 7-12 4-16

Adjustment Mechanical STRAW WALKER

No. of Straw Walker 5 5 No. of Steps 3770 Length (mm) Width (mm) 234

**CLEANING** 

Area (m2)

1.33 Upper Sieve Area Lower Sieve Area 1.35

CAPACITY

Grain Tank (m) 2.7 Fuel Tank (Lt.) 370

**BATTERY** 

No. of Batteries

Capacity & Rating of each 12V. 100Ah

**Ply Rating TYRE** Size 18.4/15x30 Front 12pr/14 pr Rear 9.00x16 16 pr

**MAIN DIMENSIONS** 

In working

Length (mm) 8300 Width (mm) 4740 Height (mm) 3810 Ground Clearance (mm) 380

In Transport

12280 Length (mm) Width (mm) 3130 Height (mm) 3810 Total Weight (K.g.) 9125 approx.

Note: As our policy of continuous development, specifications, and performance can be changed without any prior notice.











8